



Rec'd PET/PTO 13 MAY 2005
10/534852

INVESTOR IN PEOPLE

**PRIORITY
DOCUMENT**
SUBMITTED OR TRANSMITTED IN
COMPLIANCE WITH RULE 17.1(a) OR (b)

The Patent Office

Concept House

Cardiff Road

Newport

South Wales

NP10 8QQ

REC'D 04 SEP 2003

WPO


PCT

I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.



Signed

Dated 25 July 2003

Best Available Copy



31 MAY 02 E7 2764-2 02820
P01/7700 0 00-0212547.4

Request for grant of a patent

(See the notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form)

The Patent Office

Cardiff Road
Newport
South Wales
NP10 8QQ

1. Your reference

P03483GB

2. Patent application

(The Pa

0212547.4

30 MAY 2002

3. Full name, address and postcode of the or of each applicant (underline all surnames)

MEDIVANCE INSTRUMENTS LIMITED
Barretts Green Road
London
NW10 7AP
England

Patents ADP number (if you know it)

If the applicant is a corporate body, give the country/state of its incorporation

GB

7550601001

4. Title of the invention

APPARATUS FOR DETERMINING
REPLENISHMENT OF CHEMICALS

5. Name of your agent (if you have one)

"Address for service" in the United Kingdom to which all correspondence should be sent (including the postcode)

LAURENCE SHAW & ASSOCIATES
Metropolitan House
1 Hagley Road, Edgbaston
Birmingham B16 8TG

Patents ADP number (if you know it)

13623001

6. If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or of each of these earlier applications and (if you know it) the or each application number

Country

Priority application number
(if you know it)

Date of filing
(day / month / year)

7. If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of the earlier application

Number of earlier application

Date of filing
(day / month / year)

8. Is a statement of inventorship and of right to grant of a patent required in support of this request? (Answer 'Yes' if:

Yes

a) any applicant named in part 3 is not an inventor, or

b) there is an inventor who is not named as an applicant, or

c) any named applicant is a corporate body.

See note (d))

Patents Form 1/77

9. Enter the number of sheets for any of the following items you are filing with this form. Do not count copies of the same document.

Continuation sheets of this form

Description	6
Claim(s)	0
Abstract	0
Drawing(s)	3

10. If you are also filing any of the following, state how many against each item.

Priority documents

Translations of priority documents

Statement of inventorship and right to grant of a patent (*Patents Form 7/77*)

Request for preliminary examination and search (*Patents Form 9/77*)

Request for substantive examination (*Patents Form 10/77*)

Any other documents
(*please specify*)

11.

I/We request the grant of a patent on the basis of this application.

Signature
Laurence Shaw & Associates
LAURENCE SHAW & ASSOCIATES

Date *29/5/02*

12. Name and daytime telephone number of person to contact in the United Kingdom

Keith Leaman

0121 454 4962

Warning

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.

Notes

- If you need help to fill in this form or you have any questions, please contact the Patent Office on 08459 500505.*
- Write your answers in capital letters using black ink or you may type them.*
- If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.*
- If you have answered 'Yes' Patents Form 7/77 will need to be filed.*
- Once you have filled in the form you must remember to sign and date it.*
- For details of the fee and ways to pay please contact the Patent Office.*

CLAIMS

1. A system for monitoring when chemicals in a development process need replenishing, the system comprising a reference strip bearing a developed graduated scale of exposure of a radiation sensitive medium to a range of exposures, a testing module comprising a radiation shielded pouch and an unexposed radiation sensitive medium within the pouch, said module including a radiation filter for producing a graduated scale of a range of exposures to radiation on a test strip when it is exposed to radiation and subsequently developed, said scale on the test strip being identical to that on the reference strip when the test strip is exposed to the same radiation and developed in a developing bath with an acceptable chemical level and composition, as that used to produce the scale on the reference strip, means for comparing the scales on the reference and test strips side-by-side, the test strip and the reference strip each having a datum indicia that align when the test strip and the reference strips are in a datum position relative to each other where the scale on the test strip matches the scale on the reference strip, and one or both strips having limits indicia that together define an acceptable range of variation of the graduated scales of the test strip compared with the test graduated scale of the reference strip when the test strip is moved relative to the graduated scale of the reference strip away from said datum position in a direction along the scale of the reference strip to bring a selected first region of the graduated scale of the test strip in alignment with a matching region of the graduated scale of the reference strip.
2. A system according to claim 1 wherein the datum indicia comprises a reference line on each strip that aligns with each other when the strips are in the datum position, and one or both of the strips have a second line spaced from the first

line in a direction measured along the direction that the scales extend that defines a limit of acceptable relative displacement of the test strip along the scale of the reference strip.

3. A system according to claim 1 or claim 2 wherein the pouch is provided with a radiation filter or mask that defines two bands of varying thickness so that when the strip is exposed to x-radiation, two graded scales of varying grey scales are produced on the strip when the film is developed.
4. A system according to claim 3 wherein the band of the filter has uniform step changes in thickness (and hence density) rather than a gradual change in thickness.
5. A system according to any one of claims 1 to 4 wherein the test strip has a numerical scale printed on it corresponding to each step change of density of the mask.
6. A system according to claim 5 wherein the test strip has indicia comprising two lines marked to indicate "safe" and "fail" at one end of the scale.
7. A system according to any one of claims 3 to 6 wherein the reference strip has identical indicia and markings to that of the test strip.
8. A system according to any one of the preceding claims wherein the pouch is incorporated in a cassette of an x-ray film plate.

THIS PAGE BLANK (USPTO)

THIS PAGE BLANK (USPTO)

9. A system according to claim 8 wherein the cassette is provided with a graduated radiation filter or mask that creates the graduated scale of the test strip on the x-ray film.
10. A method of testing when chemicals in a development process need replenishing comprising the steps of:
 - a) providing a system according to any one of claims 1 to 7;
 - b) placing a test strip in the sealed pouch and exposing the sealed pouch to x-radiation;
 - c) removing the test strip from the pouch in a darkroom environment and processing the test strip in a development bath the composition and contents of which is to be tested to produce a developed test strip;
 - d) comparing the developed test strip with the reference strip by laying the strips alongside each other;
 - e) moving one strip relative to the other in a direction along the graduated scales until a selected region of the graduated scales of the test strip matches a selected region of the graduated scale of the reference strip and thereby establish a matched position;
 - f) comparing the position of datum indicia of one of the strips with the limits indicia of the other strip when the strips are in said matched position, and
 - g) assessing whether the datum indicia of one strip is between the limits indicia of the other strip thereby to assess whether the chemicals in the processing bath need replenishing.
11. A method according to claim 10 wherein the reference strip is fixed in place on an illuminated background and the test strip is moved axially relative to the reference

strip until one of the density steps matches one of the density steps of the reference strip.

12. A method according to claim 10 or claim 11 wherein the datum indicia is a reference line and the limits indicia comprise the reference line and a second line.

KL/JW/P03483GB
March 12, 2003

Agents Ref: P03483GB

APPARATUS FOR DETERMINING REPLENISHMENT OF CHEMICALS

This invention relates to photographic and x-ray processing and is particularly concerned in monitoring when the chemicals used in the development process need replenishing in order to ensure uniformity and reliability of the developing process. This is more of a problem with x-ray processing where large numbers of x-ray images are being produced and the interpretation of crucial features of the x-ray images are dependent upon clarity of feint or obscured details of the x-ray image.

As the levels of chemicals of the developing bath are depleted or the composition changes, the quality of the resulting x-ray images also degrade and there is no reliable way of telling if quality of the image is poor as a result of imperfect development. Therefore important aspects of the x-ray could be missed when looking at the x-ray image that is indistinct due to poor processing.

One way of testing whether the chemicals in the developing bath needs replenishing is to run a test exposure of a reference image at the start of a development process, for example at the start of a shift or beginning of a day. However, this would not give any indication of the levels of chemicals or their composition throughout the day.

An object of the present invention is to provide an easy to use apparatus and method for monitoring the efficacy of an x-ray or photographic development process.

According to one aspect of the present invention there is provided a system for monitoring when chemicals in a development process need replenishing, the system comprising a reference strip bearing a developed graduated image of exposure of a

radiation sensitive medium to a range of exposures, a testing module comprising a radiation shielded pouch and an unexposed radiation sensitive medium within the pouch, said module including a radiation filter for producing on the test strip, when it is exposed to radiation and subsequently developed, a graduated scale of a range of exposures to radiation, said scale on the test strip being identical to that on the reference strip when the test strip is exposed to the same radiation as that used to produce the reference scale and developed in a developing bath with an acceptable chemical level and composition as that used to produce the reference scale, means for comparing the strips side-by-side, the test strip and the reference strip each having indicia that align when the test strip and the reference strips are in a datum position where the scale on the test strip matches the scale on the reference strip, and one or both strips having indicia that together define an acceptable range of variation of the developed graduated scales of the test strip when the test graduated scale of the test strip is moved relative to the graduated scale of the reference strip away from said datum position and along the scale of the reference strip so as to bring a first region of the graduated scale of the test strip in alignment with a second region of the graduated scale of the reference strip.

Preferably, the indicia comprises a reference line on each strip that align with each other when the strips are in the datum position, and one or both of the strips have a second line spaced from the first line in a direction measured along the direction that the scales extend that defines a limit of acceptable relative displacement of the test strip along the scale of the reference strip.

The invention will now be described, by way of an example, with reference to the accompanying drawings in which:

Figures 1 to 4 illustrate a portable testing kit constructed in accordance with the present invention, and

Figure 5 illustrates a second embodiment of the invention.

Referring to Figure 1, there is shown schematically a light proof pouch 10 that contains an undeveloped test control strip 11 of x-ray film. The pouch is provided with a radiation filter or mask 12 that defines two bands 13 of varying thickness so that when the strip 11 is exposed to x-radiation, two graded scales of varying grey scales are produced on the strip when the film is developed. Preferably the band 13 of the filter has uniform step changes in thickness (and hence density) rather than a gradual change in thickness. These step changes are represented in Figure 1 by the dotted rectangles. The mask 12 is designed so that when there is the correct level of chemicals in the developing bath at the correct composition, the strip 11 will display two parallel scales 14 exhibiting step changes in when the film is developed. The test strip 11 has a numerical scale of 1 to 21 printed on it (this may be produced by modifying the mask 12 so that the numerical scale is produced during exposure of the strip 11 to x-rays). The numbers 1 to 21 correspond to each step change of density of the mask 12 and are on an arbitrary scale.

The test strip 11 also has indicia comprising two lines marked "S" and "F" at one end of the scale.

An identical reference strip 15 is produced and developed. Like the test strip 11 the reference strip 15 has two identical scales 16 of graded grey levels or contrasts and a numerical scale of 1 to 21. The reference strip has indicia in the form of a reference

line 17 marked at one end of the scales 16. The strip 15 could have two spaced lines S and F identical to those on the test strip 11.

In use, the sealed pouch 10 containing the test strip 11 is exposed to x-radiation and the strip 11 is then removed from the pouch in a darkroom or daylight loading box, and processed in the developing bath. The processed strip 11 is then compared with a reference strip 15 by laying it along side the reference strip.

The reference strip 15 is fixed in place on an illuminated background 9 and the test strip is moved axially relative to the reference strip until one of the density steps matches one of the density steps of the reference strip. The circles 15(a) show this in Figures 3 and 4.

If the reference line 17 on the reference strip 15 corresponds to the letter "S" or is between the lines "S" (Safe) and "F" (Fail) on the test strip 11, as shown in Figure 3, then the level of chemicals and the composition of the chemicals in the developing bath is acceptable.

If the reference line 17 on the reference strip 15 aligns with the line "F" on the test strip, or is outside the range of "S" to "F" on the test strip 11, as shown in Figure 4, then the developing bath chemicals "fail" and must be replenished with fresh chemicals.

In a second embodiment shown in Figure 5 the test strip 11 is incorporated in the sealed pouch or cassette 18 of the x-ray film along one edge of the film. Either the sealed cassette 18 itself is provided with a graduated radiation filter or mask 19 identical to the filter 12 of Figure 1, or a separate filter 19 is inserted inside the cassette 18 with the film prior to exposure. When the x-ray film is exposed to x-rays and

subsequently developed, the developed x-ray image will incorporate its own test strip 20. This test strip 20 is then compared with a reference strip 15 in the same way as explained above.

This latter embodiment has the advantage that anyone looking at the x-ray image can see if the developing bath was acceptable at the time the x-ray was developed. This may make it easier to interpret x-ray images where the detail is not that good.

It is to be understood that the reference line 17 could be provided on the test strip and the lines "S" and "F" could be provided on the reference strip 15. In either case, the relative positions of the line 17 and the lines "S" and "F" are set so that the reference line 17 falls between "S" and "F" when the chemical levels and composition of the developing bath is acceptable, and falls outside this range when they are not.

In a further embodiment, the test strip may be used in combination with a liquid crystal display panel of the type that includes an x-ray and light shielded display panel on which patient's details are displayed. With this type of display the data for the displayed image (for example patient's name, date of x-ray, name of consultant, etc.) is entered into the memory of the device so that the details are displayed on an LCD panel against a dark background. The displayed image exposes the x-ray film inside the shielding so that when subsequently developed, the film displays the patient's details. The present invention may be used in three ways with such a display system. In the first way a test strip 11 in accordance with Figure 1 is placed inside a light-proof pouch 10 and laid alongside the LCD display where it will be exposed to the x-rays (i.e. outside the shielding of the display panel).

In a second way the LCD display may incorporate a strip of varying stepped brightness levels corresponding to the step changes of the grey scales in the final developed test strip image so that when the film is exposed and subsequently developed, the test strip of Figure 1 is produced on the developed x-ray film.

In a third way, a photographic mask is used inside the x-ray and light shielded region adjacent the LCD panel to mask part of the unexposed x-ray film. The x-ray film is exposed by exposing the masked film to a uniform source of light (which could be generated by the LCD display) so as to produce, in the developed x-ray film, the test strip shown in Figure 1. This test strip is then compared with the reference strip.

Fig. 2




Fig. 3





Fig. 4






FIG 1

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☒ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☒ FADED TEXT OR DRAWING
- ☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☒ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.